



Economic Review and Environmental Benefits of Bioethanol

Rozita Kaviani^{a,*}

^a Department of Chemical engineering, Shiraz Branch, Islamic Azad University, Shiraz, Iran

ARTICLE INFO

Article history:

Received

Received in revised form

Accepted

Available online

ABSTRACT

In recent years, much attention has been paid to the conversion of biomass to bioethanol. Biological energies are renewable fuels with minimal pollution and play an important role in reducing greenhouse gas pollution. One of them is bioethanol, which is obtained from fermentation operations. The world's attention to the use of it as an energy source is focused on reducing the cost of production and increasing the efficiency of the ethanol industry. Ethanol or ordinary alcohol with the formula C_2H_5-OH can be used with cheap or inexpensive cellulosic sources, Such as straw, wood chips, agricultural residues, or relatively valuable carbon sources such as sugar beet molasses or sugarcane molasses, or quite valuable carbon sources such as sugar and starch. Agricultural waste is mainly composed of cellulose. In this paper, while introducing the sources of bioethanol production, its economic and environmental justification is used and its use as a green fuel in cars is discussed.

1. Introduction

Ethanol can now be considered as a reliable source of fuel. Ethanol can be produced in any country according to the resources of that country [1]. For example, in Iran they get molasses, in the United States from corn, in Europe from potatoes and ... ethanol [2]. Oil and its related products cause a lot of damage to the environment and human health [3], and the treatment of diseases requires a lot of money, which harms the country's economy [4]. Despite the fact that factories and power plants are very few in number and their operation is very easy to control, but the number of cars in the world that use oil and gasoline fuels is very large and it is impossible to control them, while the means of transportation. The main cause of greenhouse gases and their dispersion in space [5].

Researchers, while studying these problems, the only possible solution is to reduce human dependence on oil and its products. It may have been a dream one day, but scientists have been using ethanol instead of fuel in cars for some time [6]. The combination of ethanol with oil in car fuel tanks helps reduce air pollution, but the main problem with this fuel is its high price. Ethanol is currently sold at a very high price, and if different countries decide to implement this plan, a lot of subsidies should be given to ethanol so that people can use it as well

[7]. By consuming ethanol fuel instead of fossil fuels, the amount of greenhouse gas emissions known to be the cause of global warming is somewhat reduced. Ethanol can be obtained from wheat, sugar, palm oil, or even edible oils obtained from fast food restaurants [8]. Access to reliable energy sources is the most important challenge facing the countries of the world in the coming decades [9]. Due to the alarming situation in the country in the field of fuel supply of cars, which in addition to the need for continuous economic measures, has caused serious environmental problems on the one hand, and a huge and unprecedented volume of research and studies in various fields. In other countries, in order to use ethanol as a fuel for cars, it is underway [10-15].

On the other hand, it is necessary to consider national measures as soon as possible with the aim of reviewing and replacing gasoline with ethanol [16].

2. Sources of alcohol production

Currently, more than 98% of the ethanol produced in the world is obtained by the method of fermentation of sugars [17]. The sugar used can be extracted from various sources such as starches, sugars, agriculture, industrial effluents and lignocellulosic sources [18]. The cost of ethanol production is highly sensitive to the price of raw materials, the cost of delivering it to the process

* Corresponding author. e-mail: rozita.kaviani@gmail.com

department, as well as the composition of the raw materials [19]. Therefore, the success of ethanol production and its competition with gasoline can depend on the geographical location of the region, type of climate, production method, properties of agricultural products and the type of waste [20]. A system based on low cost of raw materials, easy access to raw materials and use of by-products may be economically justified [21-23].

2-1. Cellulose Sources

With the advancement of technology, there is a global potential for the use of lignocellulosic materials and their conversion to alcohol through fermentation. Mass production of cellulosic materials from various carbohydrates is common all over the world, and much research is being done on the industrialization of lignocellulosic materials and their conversion to ethanol. Of course, the technical and economic problems in the field of hydrolysis to its constituent monosaccharides have a great impact on the feasibility of ethanol production [24].

In order to be economical and effective on an industrial scale, special considerations such as comprehensive process development, product segregation, and recovery use of by-products must be considered. The crystalline and viscous nature of cellulose and its resistance to various methods of hydrolysis and production of fermentable sugars has become the focus of research and development for the economical production of ethanol from cellulosic materials [25-29].

2-2. Agricultural Derivatives

The amount of waste production and waste of agricultural products in the world is very high and due to their composition, it has become a suitable source [30]. The return of these wastes to the soil paves the way for increasing fertility, controlling erosion, releasing the required materials for the soil and stabilizing its structure [31]. The seasonality of these products and their dispersion increase costs [32]. One of the major sources of cellulosic material in developed countries is household waste [33]. In 1980, the daily production of this waste in the United States was 28×1.5 tons, of which 58% was cellulose. In the United States and Canada, it is possible to produce ethanol from municipal solid waste on a commercial scale [34].

1- Environmental benefits of using ethanol

1. Reducing CO₂ emissions: CO₂ from gasoline or any other fuel enters the atmosphere and this gas intensifies the greenhouse effect, while CO₂ from bioethanol fuel and produced in the fermentation process by plants

planted to produce ethanol will be absorbed and this is a great advantage for using bioethanol as a fuel that is not found even in clean fuels such as natural gas (Figure 1).

2. Reduction of CO and CH emissions: 10-E, 5-E and 7-E fuels have been shown to reduce CO by 4-15% and CH by 2-7%.

3. Reduced particulate matter (PM10) emissions: Suspended particles less than 10 mm in diameter that accumulate in the air sacs of six people and cause damage to the respiratory system and cancer. In ethanol-containing fuels, the emission of suspended particles is reduced by about 10%.

4. Sulfur oxides (SOX): If bioethanol is used as a pure fuel, it has no sulfur, so we have no acid, and less SOX is produced in ethanol-containing fuels.

5. Nitrogen oxides (NOX): This factor increases up to 10% in ethanol-containing fuels. As the amount of ethanol in gasoline increases, the amount of NOX decreases. By adjusting the engine and combustion temperature, this factor can be kept at the desired level.

6. Aromatics: Ethanol does not contain any aromatics. Lead-free gasolines, on the other hand, are 45% aromatic.

7. Aldehydes: The amount of acetaldehyde in ethanol-containing fuels increases. This factor can be eliminated by using a catalytic converter.

8. Increase in octane number: Table (1) shows this.

9. Alcohol safety: Ethanol is safer than gasoline, ignites later, burns more easily against a flame, and produces less smoke than gasoline.

Table 1. The effect of adding ethanol on increasing octane number [35].

The rate of increase in octane number	Octan No.	Ethanol volume percentage added	Basic gasoline octane number

3. Economic justification for using bioethanol

A study of the trend of gasoline replacement by ethanol in the world shows that while in 1975, world production of ethanol as a fuel was almost zero, in 2003 this amount reached about 30 billion liters. The largest increase was in the United States and the lowest in Europe. Europe has not shown much interest in replacing gasoline with alcohol due to its economic policies, but in recent years it has tried hard to make up for its delay and neglect. Also, it has begun to develop ethanol production as rapidly as possible.

The former US president, in one of his speeches, emphasized the cessation of oil imports from the Middle East region until 2020 and the production of bioethanol as an alternative, while the former British Prime Minister before the summit of the eight industrialized countries in Moscow in July 2006, energy has been declared the most important challenge facing this country [36].

The United States and Brazil are the largest producers of ethanol in the world. The United States alone currently produces about 19 billion liters a year, and Brazil alone more than 12 billion liters. Europe with about 500 million liters and Asia with 400 million liters are in the next categories. Most of the ethanol produced in the United States is currently based on corn, but the country's main program is the production of ethanol from cellulosic material. It helped two major industrial enzyme companies, Novozyme and Genencore, to improve the performance of industrial cellulose-digesting enzymes. Iogen Canada also received \$ 21.1 million from the Government of Canada, \$ 46 million from Shell and \$ 24.7 million from Petro Canada to cover research costs for ethanol production from cellulose.

In Canada alone, which is preparing to become the world's largest exporter of ethanol, the cellulose ethanol market is projected to reach more than \$ 10 billion by 2012.

There are currently 110 alcohol factories in the United States, 15 of which produce more than 200 million liters of alcohol per year. Another 30 plants are under construction with a production of 6.7 billion liters of ethanol. The country is already ahead of its national ethanol production plan, because while it was expected to reach an annual production of 7.5 billion gallons of ethanol by 2012, ethanol production is now approaching that level [37].

The expansion of ethanol production is expected to create about 240,000 new jobs, with a nearly \$ 43 billion increase in household incomes. There are now more than 5 million E85-powered cars in the United States (fuel containing 85% alcohol and 15% gasoline), and the number of fuel stations in the country is 650, a threefold increase over 2004. Gives. General Motors and Ford have now launched cars that can use pure ethanol fuel [38-40]. In our country, there are over 39 alcohol factories that face many problems and often suffer from equipment wear and tear and all use molasses to produce alcohol. The oldest factory in Iran currently produces 6 million liters of alcohol per year, while the capacity of the newest, located near Ahvaz, is about 30 million liters per year. 76

million liters of gasoline per day in the country, of which 30 million liters are imported, Is another fact in the country [41].

In recent years, compared to last year, gasoline consumption has increased by about 1 million liters per day [42]. The highest increase is related to the city of Tehran with 400 thousand liters per day. One of the most important challenges that has now occupied the minds of men in government and parliament is how to provide the necessary costs to import this volume of gasoline in a sustainable and sustainable way. One of the solutions to many environmental problems and water pollution, soil and especially the air in the cities of the country, which is due to the density of cars, is the use of clean fuels such as ethanol [43].

Only water and carbon dioxide are the fuel of ethanol, and the compounds sulfur, nitrogen, lead, aromatic compounds, and other carcinogens will be largely removed from people's lives. Replacing even 5% of gasoline with ethanol, which is not a problem in current car engines, will reduce gasoline imports by 12.7%, while other countries have long-term plans to reduce their imports by even one percent. They run expensive. In addition, the favorable price of ethanol compared to gasoline should be considered [44-48].

Although the country's gas resources are considered as a substitute for gasoline, it is clear that the economic justification for this is acceptable only in special circumstances, and in addition, pollution from the consumption of natural gas or CNG is estimated even more than gasoline [49].

In any case, it is necessary to start a national program in Iran to study the effects of gasoline replacement by bioethane and in line with research from other countries, in order to answer the following questions in the first place with accurate expertise:

- 1- The effects of this alternative on the domestic market and its economic justification [50].
- 2- Technological needs including necessary changes, albeit minor, in internal combustion engines, refueling stations, storage and transportation of bioethanol [51].
- 3- The positive effects of the environment, abandoning gasoline consumption and turning to ethanol [52].
- 4- Study of the country's carbon resources (including cellulose sources, molasses, starch and whey) and conversion technologies of each and the required amounts of carbon sources [53].

5- Study of job creation, creation and development of bioethanol industry, how to allocate public and private financial resources, and its social effects [54].

6- Investigating the international economic-political effects of gasoline substitution by bioethanol in the world, region and country. It should not be overlooked that the country's ethanol production industries are among the oldest and only need to pay enough attention to their product, whose real value the world is rediscovering. Developing a national ethanol program and harnessing the scientific potential of domestic research organizations and universities is the only way to help us achieve this clean renewable energy source [55].

Table 2. World Ethanol Programs [54].

Fuel consumption containing a mixture of 25% ethanol, tax deduction	Brazil
Fuels containing 5% ethanol in the next 5 years	Argentina
Forcing 10% ethanol in fuel consumption in Bangkok	Thailand
All gasoline fuels must contain 5% ethanol	India
Optionally, fuels will contain up to 10% ethanol	Australia
A subsidy of 36 cents per liter of ethanol is paid	United Kingdom
In 2010, 5.75% of the fuel (in terms of energy) should be ethanol	European Union
It has been subsidizing ethanol production since 1992	Canada

4. Discussion and Conclusion

Ethanol-burning cars reduce the impact on the car engine and increase energy efficiency. Pure ethanol has an octane number of 113, which after mixing with gasoline can provide the required octane number of unleaded gasoline and allows more compression of internal combustion engines. Ethanol is also a moisture absorber and prevents gasoline from cooling too much in winter and eliminates the need for expensive and sometimes harmful fuel additives. In addition, ethanol has cleansing properties, making engine operation easier and smoother, and facilitating and cleaning fuel injection. Ethanol is not known as a toxic substance and its inhalation is not dangerous. Its flammability is much lower than gasoline, and its storage, transport and transportation are much safer than gasoline. Ethanol itself is a completely clean fuel, thus reducing all gasoline pollutants in proportion to the percentage it is mixed with. Regarding the reduction of gases affecting the ozone

layer and the Earth's atmosphere, in estimating the benefits of this economic and industrial development, it can be said that reducing environmental damage and greenhouse gas emissions, preventing global warming and employment are among the main achievements of this project. In addition, he will not leave the country for the implementation of this currency plan. In addition, in our country, Iran, due to the potential sources of raw materials for the production of ethanol from sugarcane and beet molasses, starchy materials such as corn, wheat and linculose such as wood waste, agricultural waste, recycled paper from waste, etc. can be provided and according to the capacity of ethanol producing factories at present, and to begin with, it is possible to plan on the production of 60 million liters of pure ethanol per year for use in the transportation sector. It is obvious that in case of creating suitable conditions and encouraging investors in this sector, considering the abundance and variety of raw materials for ethanol production in the country, the operation of ethanol factories under construction and completion of production will increase to the desired level.

References

- [1] A. Ahmadpour, A. Haghigiasl, and N. Fallah. Investigation of spent caustic wastewater treatment through response surface methodology and artificial neural network in a photocatalytic reactor. *Iranian Journal of Chemical Engineering (IJChE)* 15.1 (2018) 46-72.
- [2] A. Bozorgian, and M. Ghazinezhad, A case study on causes of scale formation-induced damage in boiler tubes. *J. Biochem. Tech*, 2, (2018) 149-153.
- [3] A. Haghigiasl, A. Ahmadpour,, and N. Fallah. "Photocatalytic treatment of spent caustic wastewater in petrochemical industries." *Advances in Environmental Technology* 2.3 (2017): 153-168.
- [4] A. Bozorgian, Provide an Approach to Reduce Computations in Power System Stability, *Journal of Engineering in Industrial Research*, 3 (2022), 25-33.
- [5] E Parandi, M. Safaripour, M. H.Abdellatif, M. Saidi, A. Bozorgian, Biodiesel production from waste cooking oil using a novel biocatalyst of lipase enzyme immobilized magnetic nanocomposite. *Fuel* 313 (2022) 123057.
- [6] A. Bozorgian, Investigation and Possibility of Applying Gas Injection Method to Increase Pressure in Well A in one of the South Iranian Oil Fields, *International Journal of New Chemistry*, 9 (2022), 1-13.
- [7] A. Samimi, A. Bozorgian, M. Samimi, An Analysis of Risk Management in Financial Markets and Its Effects, *Journal of Engineering in Industrial Research*, 3 (2022), 1-7
- [8] A. Bozorgian, Exergy Analysis for Evaluation of Energy Consumptions in Hydrocarbon Plants, *International Journal of New Chemistry*, 8 (2021), 329-344.
- [9] S. Rezaniaa, S. Mahdinia, B. Oryani, J. Cho, EE. Kwon, A. Bozorgian, H. Rashidi Nodeh, N. Darajeh, and K. Mehranzamir. Biodiesel production from wild mustard (*Sinapis Arvensis*) seed oil using a novel heterogeneous catalyst of LaTiO₃ nanoparticles. *Fuel* 307 (2022), 121759.
- [10] A. Bozorgian, A review of Investigation of the Formation Kinetics of TBAC-like Clathrate Dual Hydrates, *Journal of Chemical Reviews* ,3 (2021), 109-120.

- [11] A. Ahmadpour, A. Bozorgian, Manufacture of Modified Protective Coating Derived from Coal Industry, *Journal of Science and Technology Research*, 1 (2021), 28-39.
- [12] A. Bozorgian, Thermodynamic Modeling of Gaseous Hydrates, *Journal of Engineering in Industrial Research*, 2 (2021), 194-201.
- [13] A. Bozorgian, An Overview of Methane Gas Hydrate Formation, *Journal of Engineering in Industrial Research*, 2 (2021), 166-177.
- [14] A. Samimi, S. Zarinabadi, A. Bozorgian, Optimization of Corrosion Information in Oil and Gas Wells Using Electrochemical Experiments, *International Journal of New Chemistry*, 8 (2021), 149-163.
- [15] A. Bozorgian, Investigation of Clathrite-Like Hydrates in the Gas Phase, *Journal of Engineering in Industrial Research*, 2 (2021), 90-94.
- [16] B. Raei, A. Bozorgian, Thermodynamic Modeling and Phase Prediction for Binary System Dinitrogen Monoxide and Propane, *Journal of Chemistry Letters*, 1 (2021), 143-148.
- [17] A. Bozorgian, Possibility of Using Gas Injection Method for Increasing Pressure in Well A: the Case of Oil Fields in Southern Iran, *Progress in Chemical and Biochemical Research*, 4 (2021), 207-219.
- [18] M. Bagheri Sadr, A. Bozorgian, An Overview of Gas Overflow in Gaseous Hydrates, *Journal of Chemical Reviews*, 3 (2021), 66-82.
- [19] A. Bozorgian, Investigation of Hydrate Formation Kinetics and Mechanism of Effect of Inhibitors on it, a Review, *Journal of Chemical Reviews*, 3 (2021), 50-65.
- [20] A. Bozorgian, Investigation of the effect of Zinc Oxide Nano-particles and Cationic Surfactants on Carbon Dioxide Storage capacity, *Advanced Journal of Chemistry, Section B: Natural Products and Medical Chemistry*, 3 (2021), 54-61.
- [21] N. Kayedi, A. Samimi, M. Asgari Bajgirani, A. Bozorgian, Enhanced oxidative desulfurization of model fuel: A comprehensive experimental study, *South African Journal of Chemical Engineering*, 35 (2021), 153-158.
- [22] A. Bozorgian, Investigation of the history of formation of gas hydrates, *Journal of Engineering in Industrial Research*, 1 (2020), 1-18.
- [23] A. Bozorgian, A. Samimi, A review of Kinetics of Hydrate Formation and the Mechanism of the Effect of the inhibitors on it, *International Journal of New Chemistry*, 8 (2020), 41-58.
- [24] A. Bozorgian, Z. Arab Aboosadi, A. Mohammadi, B. Honarvar, A. Azimi, Determination of CO₂ gas hydrates surface tension in the presence of nonionic surfactants and TBAC, *Revue Roumaine de Chimie*, 65 (2020), 1061-1065.
- [25] M. Bagheri sadr, A. Bozorgian, Decomposition of Hydrates in the Pipeline, *International Journal of Advanced Studies in Humanities and Social Science*, 9 (2020), 252-261.
- [26] A. Bozorgian, Investigating the Unknown Abilities of Natural Gas Hydrates, *International Journal of Advanced Studies in Humanities and Social Science*, 9 (2020), 241-251.
- [27] A. Bozorgian, Effect of Additives on Hydrate Formation, *International Journal of Advanced Studies in Humanities and Social Science*, 9 (2020), 229-240.
- [28] A. Bozorgian, Investigation of Well Equipment in the Oil Industry, *International Journal of Advanced Studies in Humanities and Social Science*, 9 (2020), 205-218.
- [29] A. Bozorgian, Z. Arab Aboosadi, A. Mohammadi, B. Honarvar, A. Azimi, Statistical Analysis of the Effects of Aluminum Oxide (Al₂O₃) Nanoparticle, TBAC and APG on Storage Capacity of CO₂ Hydrate Formation, *Iranian Journal of Chemistry and Chemical Engineering*, (2020).
- [30] A. Bozorgian, Methods of Predicting Hydrates Formation, *Advanced Journal of Science and Engineering*, 1 (2020), 34-39.
- [31] A. Bozorgian, Z. Arab Aboosadi, A. Mohammadi, B. Honarvar, A. Azimi, Optimization of determination of CO₂ gas hydrates surface tension in the presence of non-ionic surfactants and TBAC, *Eurasian Chemical Communications*, 2 (2020), 420-426.
- [32] S.E. Mousavi, A. Bozorgian, Investigation the Kinetics of CO₂ Hydrate Formation in the Water System+ CTAB+ TBAF+ ZnO, *International Journal of New Chemistry*, 7 (2020), 195-219.
- [33] A. Bozorgian, S. Zarinabadi, A. Samimi, Optimization of Well Production by Designing a Core pipe in one of the Southwest oil Wells of Iran, *Journal of Chemical Reviews*, 2 (2020), 122-129.
- [34] A. Bozorgian, Z. Arab Aboosadi, A. Mohammadi, B. Honarvar, A. Azimi, Evaluation of the effect of nonionic surfactants and TBAC on surface tension of CO₂ gas hydrate, *Journal of Chemical and Petroleum Engineering*, 54 (2020), 73-81.
- [35] A. Bozorgian, Investigation of Hydrate Formation Phenomenon and Hydrate Inhibitors, *Journal of Engineering in Industrial Research*, 1 (2020), 99-110.
- [36] A. Bozorgian, Investigation of Predictive Methods of Gas Hydrate Formation in Natural Gas Transmission Pipelines, *Advanced Journal of Chemistry, Section B*, 2 (2020), 91-101.
- [37] A. Bozorgian, Analysis and simulating recuperator impact on the thermodynamic performance of the combined water-ammonia cycle, *Progress in Chemical and Biochemical Research*, 3 (2020), 169-179.
- [38] A. Bozorgian, Study of the Effect Operational Parameters on the Supercritical Extraction Efficient Related to Sunflower Oil Seeds, *Chemical Review and Letters*, 3 (2020), 94-97.
- [39] A. Bozorgian, Investigation and Comparison of Experimental Data of Ethylene Dichloride Adsorption by Bagasse with Adsorption Isotherm Models, *Chemical Review and Letters*, 3 (2020), 79-85.
- [40] A. Bozorgian, S. Zarinabadi, A. Samimi, Preparation of Xanthan Magnetic Biocompatible Nano-Composite for Removal of Ni²⁺ from Aqueous Solution, *Chemical Methodologies*, 4 (2020), 477-493.
- [41] A. Bozorgian, Z. Arab Aboosadi, A. Mohammadi, B. Honarvar, A. Azimi, Prediction of Gas Hydrate Formation in Industries, *Progress in Chemical and Biochemical Research*, 3 (2020), 31-38.
- [42] J. Mashhadizadeh, A. Bozorgian, A. Azimi, Investigation of the kinetics of formation of Clathrite-like dual hydrates TBAC in the presence of CTAB, *Eurasian Chemical Communication*, 2 (2020), 536-547.
- [43] A. Samimi, K. Kavosi, S. Zarinabadi, A. Bozorgian, Optimization of the Gasoline Production Plant in order to Increase Feed, *Progress in Chemical and Biochemical Research*, 3 (2020), 7-19.
- [44] M.E. Bidhendi, Z. Asadi, A. Bozorgian, A. Shahhoseini, M.A. Gabris, New Magnetic Co₃O₄/Fe₃O₄ Doped Polyaniline Nanocomposite for the Effective and Rapid Removal of Nitrate Ions from Ground Water Samples, *Environmental Progress & Sustainable Energy*, (2020).

- [45] A. Pourabadeh, B. Nasrollahzadeh, R. Razavi, A. Bozorgian, M. Najafi, Oxidation of FO and N₂ molecules on the surfaces of metal-adopted boron nitride nanostructures as efficient catalysts, *Journal of Structural Chemistry*, 59 (2018), 1484-1491.
- [46] A. Surendar, A. Bozorgian, A. Maseleno, L.K. Ilyashenko, M. Najafi, Oxidation of toxic gases via GeB36N36 and GeC72 nanocages as potential catalysts, *Inorganic Chemistry Communications*, 96 (2018), 206-210.
- [47] A. Bozorgian, The Production of Clay Nano-Composite Epoxy and Comparison of Its Properties with Epoxy Resins, *Journal of Basic and Applied Scientific Research*, 12 (2012), 2923-12929.
- [48] N. Farhami, A. Bozorgian, Factors affecting selection of tubes of heat exchanger, *Int. Conf. on Chem. and Chem. Process IPCBEE*, 10, 223-228.
- [49] A. Bozorgian, N.M. Nasab, H. Mirzazadeh, Overall Effect of Nano Clay on the Physical Mechanical Properties of Epoxy Resin, *World Academy of Science, Engineering and Technology International Journal of Materials and Metallurgical Engineering*, (2011).
- [50] A. Bozorgian, NM. Nasab, A. Memari, Buckling analysis of a five-walled CNT with nonlocal theory, *interaction* 1 (2011), 4.
- [51] B. Raei, A. Ghadi, A. Bozorgian, Heat Integration of heat exchangers network using pinch technology, 19th International Congress of Chemical and Process Engineering CHISA, (2010).
- [52] A. Bozorgian, P. KHADIV Parsi, MA. Mousavian, Experimental Study of Simultaneous Effect of Surfactant and Salt on Drop-Interface Coalescence, *Nashrieh Shimi va Mohandes Shimi Iran*, 27 (4), 59-68.
- [53] A.H. Tarighaleslami, A. Bozorgian, B. Raei, Application of the exergy analysis in the petroleum refining processes optimization, *The 1st Territorial Chemistry and Industry Symposium, Lecture number: E-1097, Damghan, Iran (in Persian)*. 2009.
- [54] A. Bozorgian, P. Khadiv Parsi, M.A. Mousavian, Simultaneous Effects of Ionic Surfactant and Salt on Drop-Interface Coalescence, *Iranian Journal of Chemical Engineering*, 6 (2009), 73-86.
- [55] B. Raei, A. Ghadi, A. Bozorgian, Heat integration of heat exchangers network using pinch technology.(2010) 19th International Congress of Chemical and Process Engineering, *CHISA 2010 and 7th European Congress of Chemical Engineering, ECCE-7*, (2010).